



jalas® EXALTER 9955

EN ISO 20345:2011 S3, SRC, HRO ASTM F2413-18 M/I/C SD 35 PR ASTM F3445-21 SR



[Learn more](#)

LOW-CUT, WATER REPELLANT WITH LACES

This low-cut safety shoe has the features you need for most work situations, such as PTC-textile nail protection, toecap in aluminum and high-grip Vibram Nitrile rubber outsole. The midsole and JALAS FX3 Supreme multilayer insole together with the sock-like construction provide ultimate comfort. PORON® XRD™ shock-absorption prevents injuries to foot and back. The upper is water repellent, perfect for those who work in wet environments.

CHARACTERISTICS

- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable
- Excellent shock absorption

FUNCTIONS

- Double shock absorption zones
- Conforms with IEC 61340-5-1 (ESD)
- Heat-resistant outsole
- Oil-resistant outsole
- Anti-static properties
- Polstered shaft edge
- Ventilating insole
- Stabilizator
- Water repellent
- Ergonomically shaped
- Soft
- Specially designed details
- Free from animal-derived materials



PREVENTS RISK OF

Toe injuries, nail penetration, sprain injuries, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, environments with risk for outsole penetration, clean environments

SPECIFICATION

TYPE Safety footwear, Low shoes

CATEGORY Cat. II

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Regular

COLLECTION Exalter

UPPER MATERIAL Microfiber, Textile

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester

INSOLE JALAS 8303 FX3 Supreme

INNERSOLE MATERIAL Textile, Soft EVA, Rigid EVA, Polyester-based conductive thread, Neo foam, Poron® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

FASTENING Laces

SHOELACES LENGTH 100 cm

COLOUR Black, Red

NET WEIGHT, (SIZE 42) 1,26 kg

COMPLIANCE



EN ISO 20345:2011
S3, SRC, HRO



ASTM F2413-18
M/I/C
SD 35 PR

TP TC 019:2011

ASTM F3445-21
SR



ÖNORM Z 1259



DGUV 112-191

FEATURES



Anti-static properties



Ergothan Shock Absorption System



ESD



Aluminium toecap



Oil-resistant outsole



Heat-resistant outsole



Water repellent



Nail protection in plasma-treated composite (PTC) textile



Stabilizator

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
34	1.5	2.5	3.5	9955-34	6408487512728
35	2	3.5	4	9955-35	6408487512735
36	3	4	5	9955-36	6408487512742
37	4	5	6	9955-37	6408487512759
38	5	5.5	6.5	9955-38	6408487512766
39	6	6.5	7.5	9955-39	6408487512773
40	6.5	7.5	8.5	9955-40	6408487512780
41	7	8	9	9955-41	6408487512797
42	8	9	10	9955-42	6408487512803
43	9	9.5	11	9955-43	6408487512810
44	10	10.5	11.5	9955-44	6408487512827
45	10.5	11	12.5	9955-45	6408487512834
46	11	12	13	9955-46	6408487512841
47	12	13	14	9955-47	6408487512858

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com