



ZENIT 1708

EN ISO 20345:2022 S1, PS, SR, FO, SC, LG



[Learn more](#)

A soft, comfortable safety sandal with highest quality (S1P) protection and BOA® Fit System for the. The PU-coated/split leather upper, and polyester and polyamid lining, keeps feet warm and safe all day. An oil-resistant RPU outer sole gives excellent grip on slippery surfaces, and JALAS® aluminium toe cap protection, plasma-treated textile puncture protection and double impact protection zones in PORON® XRD®.

CHARACTERISTICS

- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable
- Excellent shock absorption
- Breathable

FUNCTIONS

- ProNose toe reinforcement
- Oil-resistant outsole
- Anti-static properties
- Polstered shaft edge
- Ventilating insole
- Conforms with IEC 61340-5-1 (ESD)
- Quick-tie
- Stabilizator
- BOA® Fit System
- Double shock absorption zones



PREVENTS RISK OF

Toe injuries, nail penetration, antistatic

PRIMARY ENVIRONMENTS OF USE

Indoors, environments with risk for outsole penetration

SPECIFICATION

TYPE Safety footwear, Sandals

CATEGORY Cat. II

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Regular

COLLECTION Zenit

UPPER MATERIAL PU-coated leather, Split leather

PRONOSE MATERIAL PU

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester, polyamide

INSOLE JALAS 8217 FX2 Climate

INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Merino wool, Double shock absorption zones in Poron® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL RPU outsole

FASTENING BOA® Fit System

COLOUR Black, Grey, Red

NET WEIGHT, (SIZE 42) 1.31 kg

COMPLIANCE



TP TC 019:2011

EN ISO 20345:2022
S1, P5, SR, F0, SC, LG



ÖNORM Z 1259



DGUV 112-191

FEATURES



Anti-static properties



Ergothon Shock Absorption System



ESD



Aluminium toecap



Oil-resistant outsole



ProNose toe reinforcement



Nail protection in plasma-treated composite (PTC) textile



Stabilizator

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
36	3	4	5	1708-36	6408487501555
37	4	5	6	1708-37	6408487501562
38	5	5½	6½	1708-38	6408487501579
39	6	6½	7½	1708-39	6408487501586
40	6½	7½	8½	1708-40	6408487501593
41	7	8	9	1708-41	6408487501609
42	8	9	10	1708-42	6408487501616
43	9	9½	11	1708-43	6408487501623
44	10	10½	11½	1708-44	6408487501630
45	10½	11	12½	1708-45	6408487501647
46	11	12	13	1708-46	6408487501654
47	12	13	14	1708-47	6408487501661

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com