

JALAS® 1228W

EN ISO 20349-2:2017, S3, SRC, WG, HRO, CI, HI

PROPRIETÀ Buona presa, extra confortevole, eccellente assorbimento shock

TAGLIE (UE) 35-48



www.jalas.com

JALAS® 1228W

EN ISO 20349-2:2017, S3, SRC, WG, HRO, CI, HI

PROPRIETÀ Buona presa, extra confortevole, eccellente assorbimento shock

TAGLIE (UE) 35-48



www.jalas.com

JALAS® 1228W

EN ISO 20349-2:2017, S3, SRC, WG, HRO, CI, HI

PROPRIETÀ Buona presa, extra confortevole, eccellente assorbimento shock

TAGLIE (UE) 35-48



www.jalas.com

JALAS® 1228W

EN ISO 20349-2:2017, S3, SRC, WG, HRO, CI, HI

PROPRIETÀ Buona presa, extra confortevole, eccellente assorbimento shock

TAGLIE (UE) 35-48



www.jalas.com

JALAS® 1228W

EN ISO 20349-2:2017, S3, SRC, WG, HRO, CI, HI

PROPRIETÀ Buona presa, extra confortevole, eccellente assorbimento shock

TAGLIE (UE) 35-48



www.jalas.com

JALAS® 1228W

EN ISO 20349-2:2017, S3, SRC, WG, HRO, CI, HI

PROPRIETÀ Buona presa, extra confortevole, eccellente assorbimento shock

TAGLIE (UE) 35-48



www.jalas.com

JALAS® 1228W

EN ISO 20349-2:2017, S3, SRC, WG, HRO, CI, HI

PROPRIETÀ Buona presa, extra confortevole, eccellente assorbimento shock

TAGLIE (UE) 35-48



www.jalas.com

JALAS® 1228W

EN ISO 20349-2:2017, S3, SRC, WG, HRO, CI, HI

PROPRIETÀ Buona presa, extra confortevole, eccellente assorbimento shock

TAGLIE (UE) 35-48



www.jalas.com

JALAS® 1228W

EN ISO 20349-2:2017, S3, SRC, WG, HRO, CI, HI

PROPRIETÀ Buona presa, extra confortevole, eccellente assorbimento shock

TAGLIE (UE) 35-48



www.jalas.com

JALAS® 1228W

EN ISO 20349-2:2017, S3, SRC, WG, HRO, CI, HI

PROPRIETÀ Buona presa, extra confortevole, eccellente assorbimento shock

TAGLIE (UE) 35-48



www.jalas.com