



SIZE	ART. NO.	EAN NO.	SIZE	ART. NO.	EAN NO.
35	1228W-35	6408487523571	47	1228W-47	6408487524059
36	1228W-36	6408487523618	48	1228W-48	6408487524097
37	1228W-37	6408487523656			
38	1228W-38	6408487523694			
39	1228W-39	6408487523731			
40	1228W-40	6408487523779			
41	1228W-41	6408487523816			
42	1228W-42	6408487523854			
43	1228W-43	6408487523892			
44	1228W-44	6408487523939			
45	1228W-45	6408487523977			
46	1228W-46	6408487524011			

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

JALAS® 1228W

EN ISO 20345:2011, EN ISO 20349-2:2017, S3, SRC, WG, HRO, CI, HI

PROPERTIES

Good grip, extra comfortable, excellent shock absorption

SPECIFICATION

TYPE OF SHOE Safety footwear, boots/Ankle boots

NAIL PROTECTION MATERIAL Steel

FITTING Regular

SIZE RANGE (EU) 35-48

PLATFORM Balance

UPPER MATERIAL PU-coated leather

UPPER MATERIAL THICKNESS 1,5-1,7

PRONOSE-MATERIAL PU

TOECAP MATERIAL Composite

LINING MATERIAL Polyamide

SOLE MATERIAL PU midsole, rubber outsole

INSOLE FX2 Supreme

INSOLE MATERIAL Textile, soft EVA, polyester-based conductive thread, double shock absorption zones in Poron® XRD®

FASTENING BOA® Fit System

COLOUR Black, Grey, Yellow

JALAS® 1228W

FEATURES

ProNose toe reinforcement, KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit), heat-resistant upper, heat-resistant outsole, oil-resistant outsole, anti-static properties, padded boot shaft, ventilating insole, BOA® Fit System, water repellent

PREVENTS RISK OF

Toe injuries, nail penetration, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, all-year use, warm surfaces, environments with risk for outsole penetration, oily and greasy environments, dirty environments, harsh environments

2(3)



Composite toecap



Heat-resistant upper



Nail protection in steel



Anti-static properties



Heat-resistant outsole



Water repellent



Oil-resistant outsole



ProNose toe reinforcement



Ergothon Shock Absorption System

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-10-04

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com



JALAS® 1228W

COMPLIANCE

EN ISO 20345:2011, EN ISO 20349-2:2017

COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S2: S1 + WRU

S3: S2 + P

WRU: Water-repellent upper

P: Penetration-resistant outsole

HRO: Heat-resistant outsole compound tested at 300°C

Cl: Cold insulation

FO: Oil-resistant outsole

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

DGUV 112-191: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

Ö-Norm Z 1259: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

CE



Composite toecap



Heat-resistant upper



Nail protection in steel



Anti-static properties



Heat-resistant outsole



Water repellent



Oil-resistant outsole



ProNose toe reinforcement



Ergothon Shock Absorption System

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-10-04

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com