



JALAS® 1278 HEAVY DUTY

EN ISO 20345:2011, S3, SRC, HRO, CI, HI

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Outdoors, indoors, all-year use, warm surfaces, environments with risk for outsole penetration, oily and greasy environments, dirty environments, harsh environments

FEATURES ProNose toe reinforcement, heat-resistant outsole, oil-resistant outsole, TPU heel support, bellows tongue, padded shaft edge in memory foam, BOA® Fit System, ankle support, pull loops, water repellent, ergonomically shaped, double shock absorption zones, conforms with IEC 61340-5-1

(ESD)

UPPER MATERIAL PU-coated leather

SOLE MATERIAL PU midsole, rubber outsole

INSOLE FX2 Supreme

FITTING Regular

SIZE RANGE (EU) 35-48



Composite toecap



ProNose toe reinforcement



Nail protection in steel



ErgoShock Absorption System



Heat-resistant outsole



Anti-static properties



Water repellent



ESD



Oil-resistant outsole



JALAS® 1278 HEAVY DUTY

EN ISO 20345:2011, S3, SRC, HRO, CI, HI

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Outdoors, indoors, all-year use, warm surfaces, environments with risk for outsole penetration, oily and greasy environments, dirty environments, harsh environments

FEATURES ProNose toe reinforcement, heat-resistant outsole, oil-resistant outsole, TPU heel support, bellows tongue, padded shaft edge in memory foam, BOA® Fit System, ankle support, pull loops, water repellent, ergonomically shaped, double shock absorption zones, conforms with IEC 61340-5-1

(ESD)

UPPER MATERIAL PU-coated leather

SOLE MATERIAL PU midsole, rubber outsole

INSOLE FX2 Supreme

FITTING Regular

SIZE RANGE (EU) 35-48



Composite toecap



ProNose toe reinforcement



Nail protection in steel



ErgoShock Absorption System



Heat-resistant outsole



Anti-static properties



Water repellent



ESD



Oil-resistant outsole