



JALAS® 1368 HEAVY DUTY

EN ISO 20345:2011, S3, SRC, HRO, CI, HI, AN

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, warm, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Outdoors, metal-free requirements for shoes, warm surfaces, environments with risk for outsole penetration, slippery environments, cold environments, moist environments, oily and greasy environments, dirty environments, harsh environments, environments with explosive risks

FEATURES ProNose toe reinforcement, heat-resistant upper, heat-resistant outsole, oil-resistant outsole, metal free, anti-static properties, bellows tongue, padded boot shaft, polstered shaft edge,

ankle protection, ankle support, pull loops, ESD, water repellent, ergonomically shaped, reflector, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

UPPER MATERIAL Microfiber, PU-coated leather
SOLE MATERIAL PU midsole, plastic shank, hNBR rubber + Gripper lugs

INSOLE FX2 Supreme

FITTING Regular

SIZE RANGE (EU) 35-48



Composite toecap



Ergothen Shock Absorption System



Nail protection in plasma-treated composite (PTC) textile



Shock absorbing



Heat-resistant outsole



Winter model



Water repellent



Anti-static properties



Oil-resistant outsole



ESD



ProNose toe reinforcement



JALAS® 1368 HEAVY DUTY

EN ISO 20345:2011, S3, SRC, HRO, CI, HI, AN

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, warm, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Outdoors, metal-free requirements for shoes, warm surfaces, environments with risk for outsole penetration, slippery environments, cold environments, moist environments, oily and greasy environments, dirty environments, harsh environments, environments with explosive risks

FEATURES ProNose toe reinforcement, heat-resistant upper, heat-resistant outsole, oil-resistant outsole, metal free, anti-static properties, bellows tongue, padded boot shaft, polstered shaft edge,

ankle protection, ankle support, pull loops, ESD, water repellent, ergonomically shaped, reflector, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

UPPER MATERIAL Microfiber, PU-coated leather
SOLE MATERIAL PU midsole, plastic shank, hNBR rubber + Gripper lugs

INSOLE FX2 Supreme

FITTING Regular

SIZE RANGE (EU) 35-48



Composite toecap



Ergothen Shock Absorption System



Nail protection in plasma-treated composite (PTC) textile



Shock absorbing



Heat-resistant outsole



Winter model



Water repellent



Anti-static properties



Oil-resistant outsole



ESD



ProNose toe reinforcement