

JALAS® 1368 HEAVY DUTY

EN ISO 20345:2011, S3, SRC, HRO, CI, HI, AN

PROPERTIES

Highest level of protection, excellent grip, perfect fit, extra comfortable, warm, excellent shock absorption

SPECIFICATION

TYPE OF SHOE Safety footwear, boots

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Regular

SIZE RANGE (EU) 35-48

COLLECTION Heavy Duty

PLATFORM Arctic Grip

UPPER MATERIAL Microfiber, PU-coated leather

UPPER MATERIAL THICKNESS 1,6-1,8

PRONOSE-MATERIAL PU

TOECAP MATERIAL Composite

LINING MATERIAL Polyester fur

SOLE MATERIAL PU midsole, plastic shank, hNBR rubber + Gripper lugs

INSOLE FX2 Supreme

INSOLE MATERIAL Textile, soft EVA, polyester-based conductive thread, Merino wool, double shock absorption zones in Poron® XRD®

FASTENING Laces

COLOUR Black, Grey



SIZE	ART. NO.	EAN NO.	SIZE	ART. NO.	EAN NO.
35	1368-35	6408487511943	47	1368-47	6408487511820
36	1368-36	6408487511936	48	1368-48	6408487511813
37	1368-37	6408487511929			
38	1368-38	6408487511912			
39	1368-39	6408487511905			
40	1368-40	6408487511899			
41	1368-41	6408487511882			
42	1368-42	6408487511875			
43	1368-43	6408487511868			
44	1368-44	6408487511851			
45	1368-45	6408487511844			
46	1368-46	6408487511837			

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

JALAS® 1368 HEAVY DUTY

FEATURES

ProNose toe reinforcement, heat-resistant upper, heat-resistant outsole, oil-resistant outsole, metal free, anti-static properties, bellows tongue, padded boot shaft, polstered shaft edge, ankle protection, ankle support, pull loops, ESD, water repellent, ergonomically shaped, reflector, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

PREVENTS RISK OF

Toe injuries, nail penetration, sprain injuries, antistatic, contact with cold, slipping

PRIMARY ENVIRONMENTS OF USE

Outdoors, metal-free requirements for shoes, warm surfaces, environments with risk for outsole penetration, slippery environments, cold environments, moist environments, oily and greasy environments, dirty environments, harsh environments, environments with explosive risks



Composite toecap



Shock absorbing



Nail protection in plasma-treated composite (PTC) textile



Winter model



Heat-resistant outsole



Anti-static properties



Water repellent



ESD



Oil-resistant outsole



ProNose toe reinforcement



Ergothon Shock Absorption System

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-10-04

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

JALAS® 1368 HEAVY DUTY

COMPLIANCE
EN ISO 20345:2011

COMPLIANCE DESCRIPTION

AN: Ankle protection

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S2: S1 + WRU

S3: S2 + P

WRU: Water-repellent upper

P: Penetration-resistant outsole

HRO: Heat-resistant outsole compound tested at 300°C

CI: Cold insulation

HI: Heat insulation

FO: Oil-resistant outsole

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

I: Footwear made from leather and other materials, excluding all-rubber or all-polymeric footwear

DGUV 112-191: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

Ö-Norm Z 1259: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



CE



Composite toecap



Shock absorbing



Nail protection in plasma-treated composite (PTC) textile



Winter model



Heat-resistant outsole



Anti-static properties



Water repellent



ESD



Oil-resistant outsole



ProNose toe reinforcement



Ergothon Shock Absorption System

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-10-04

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com