

## JALAS® 1558 GP

EN ISO 20345:2011, S3, SRC, HRO, CI, HI

### PROPERTIES

Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

### SPECIFICATION

TYPE OF SHOE Safety footwear, low shoes

NAIL PROTECTION MATERIAL Steel

FITTING Wide

SIZE RANGE (EU) 35-50

COLLECTION Gran Premio

PLATFORM Enduro

UPPER MATERIAL Cordura®, PU-coated leather

UPPER MATERIAL THICKNESS 1,6-1,8

PRONOSE-MATERIAL PU

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyamide

SOLE MATERIAL PU midsole, rubber outsole

INSOLE FX2 Supreme

INSOLE MATERIAL Textile, soft EVA, polyester-based conductive thread, Merino wool, double shock absorption zones in Poron® XRD®

FASTENING BOA® Fit System

COLOUR Black, Grey, Yellow



SIZE	ART. NO.	EAN NO.	SIZE	ART. NO.	EAN NO.
35	1558-35	6408487513824	47	1558-47	6408487514067
36	1558-36	6408487513848	48	1558-48	6408487514081
37	1558-37	6408487513862	49	1558-49	6408487514104
38	1558-38	6408487513886	50	1558-50	6408487514128
39	1558-39	6408487513909			
40	1558-40	6408487513923			
41	1558-41	6408487513947			
42	1558-42	6408487513961			
43	1558-43	6408487513985			
44	1558-44	6408487514005			
45	1558-45	6408487514029			
46	1558-46	6408487514043			

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## JALAS® 1558 GP

### FEATURES

ProNose toe reinforcement, wide fit, heat-resistant outsole, oil-resistant outsole, anti-static properties, bellows tongue, polstered shaft edge, ventilating insole, BOA® Fit System, water repellent, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

### PREVENTS RISK OF

Toe injuries, nail penetration, antistatic

### PRIMARY ENVIRONMENTS OF USE

Outdoors, warm surfaces, environments with risk for outsole penetration, oily and greasy environments, harsh environments

2(3)

CE



Aluminium toecap



Ergothan Shock Absorption System



Nail protection in steel



Anti-static properties



Heat-resistant outsole



ESD



Water repellent



Oil-resistant outsole



ProNose toe reinforcement



Wide fit

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-10-04

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

## JALAS® 1558 GP

**COMPLIANCE**  
EN ISO 20345:2011

### COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S2: S1 + WRU

S3: S2 + P

WRU: Water-repellent upper

P: Penetration-resistant outsole

HRO: Heat-resistant outsole compound tested at 300°C

CI: Cold insulation

HI: Heat insulation

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

DGUV 112-191: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

Ö-Norm Z 1259: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



CE



Aluminium toecap



Nail protection in steel



Heat-resistant outsole



Water repellent



Oil-resistant outsole



ProNose toe reinforcement



Wide fit



Ergothen Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-10-04

3(3)

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com