



JALAS® 1578 FIRE RESCUE

EN 15090:2012, F1PA, SRC, CI

PROPERTIES

Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

SPECIFICATION

TYPE OF SHOE Safety footwear, boots

NAIL PROTECTION MATERIAL Steel

FITTING Wide

SIZE RANGE (EU) 38-50

COLLECTION Fire

PLATFORM Enduro

UPPER MATERIAL PU-coated leather

UPPER MATERIAL THICKNESS 1,6-1,8

PRONOSE-MATERIAL PU

TOECAP MATERIAL Aluminium

LINING MATERIAL Drylock membrane, polyester, polyamide

SOLE MATERIAL PU midsole, rubber outsole

INSOLE FX2 Pro

INSOLE MATERIAL Textile, soft EVA, polyester-based conductive thread, double shock absorption zones in Poron® XRD®

COLOUR Black, Yellow

SIZE	ART. NO.	EAN NO.
49	1578-49	6408487503818
50	1578-50	6408487503825

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

JALAS® 1578 FIRE RESCUE

FEATURES

ProNose toe reinforcement, wide fit, KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit), heat-resistant upper, heat-resistant outsole, oil-resistant outsole, anti-static properties, padded boot shaft, ventilating insole, pull loops, waterproof, reflector, specially designed details, double shock absorption zones

PREVENTS RISK OF

Toe injuries, nail penetration, antistatic, wet feet

PRIMARY ENVIRONMENTS OF USE

Outdoors, all-year use, warm surfaces, environments with risk for outsole penetration, moist environments, oily and greasy environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Fire fighting, mining, rescue work



Aluminium toecap



Ergothan Shock Absorption System



Nail protection in steel



Heat-resistant upper



Heat-resistant outsole



Anti-static properties



Waterproof



Oil-resistant outsole



ProNose toe reinforcement



Wide fit

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

JALAS® 1578 FIRE RESCUE

COMPLIANCE
EN 15090:2012

COMPLIANCE DESCRIPTION

WR: Water-resistant footwear

P: Penetration-resistant outsole

HRO: Heat-resistant outsole compound tested at 300°C

CI: Cold insulation

HI: Heat insulation

A: Electrical resistance (between 0.1-1000 Mega Ohms

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

DGUV 112-191: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

Ö-Norm Z 1259: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



CE



Aluminium toecap



Ergothon Shock Absorption System



Nail protection in steel



Heat-resistant upper



Heat-resistant outsole



Anti-static properties



Waterproof



Oil-resistant outsole



ProNose toe reinforcement



Wide fit

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-10-04

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com