



jalas®



JALAS® 1848K TITAN

EN ISO 20345:2011, S3, SRC, HRO, CI, HI

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Outdoors, indoors, all-year use, warm surfaces, environments with risk for outsole penetration

FEATURES ProNose toe reinforcement, Thinsulate™ heat insulation, wide fit, KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit), heat-resistant upper, heat-resistant outsole, oil-resistant outsole, anti-static properties, padded boot shaft, ventilating insole, pull loops, water repellent, double shock

absorption zones

UPPER MATERIAL PU-coated leather

SOLE MATERIAL PU midsole, plastic shank, rubber outsole

INSOLE FX2Pro

FITTING Wide

SIZE RANGE (EU) 35-50

CE



Aluminium toecap



ProNose toe reinforcement



Nail protection in plasma-treated composite (PTC) textile



Wide fit



Heat-resistant outsole



Ergothon Shock Absorption System



Water repellent



Heat-resistant upper



Oil-resistant outsole



Anti-static properties



jalas®



JALAS® 1848K TITAN

EN ISO 20345:2011, S3, SRC, HRO, CI, HI

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Outdoors, indoors, all-year use, warm surfaces, environments with risk for outsole penetration

FEATURES ProNose toe reinforcement, Thinsulate™ heat insulation, wide fit, KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit), heat-resistant upper, heat-resistant outsole, oil-resistant outsole, anti-static properties, padded boot shaft, ventilating insole, pull loops, water repellent, double shock

absorption zones

UPPER MATERIAL PU-coated leather

SOLE MATERIAL PU midsole, plastic shank, rubber outsole

INSOLE FX2Pro

FITTING Wide

SIZE RANGE (EU) 35-50

CE



Aluminium toecap



ProNose toe reinforcement



Nail protection in plasma-treated composite (PTC) textile



Wide fit



Heat-resistant outsole



Ergothon Shock Absorption System



Water repellent



Heat-resistant upper



Oil-resistant outsole



Anti-static properties