

## JALAS® 1872 OFF ROAD

EN ISO 20347:2012, 02, SRC, HRO, CI, FO

### PROPERTIES

Excellent grip, perfect fit, extra comfortable, excellent shock absorption

### SPECIFICATION

TYPE OF SHOE Occupational footwear, boots/Ankle boots

FITTING Wide

SIZE RANGE (EU) 36-48

COLLECTION Gran Premio

PLATFORM Enduro

UPPER MATERIAL PU-coated leather

UPPER MATERIAL THICKNESS 1,6-1,8

LINING MATERIAL Technical fleece

SOLE MATERIAL PU midsole, plastic shank, rubber outsole

INSOLE FX2 Pro

INSOLE MATERIAL Textile, soft EVA, polyester-based conductive thread, double shock absorption zones in Poron® XRD®

FASTENING Laces, Zipper

COLOUR Black, Grey, Yellow



SIZE	ART. NO.	EAN NO.	SIZE	ART. NO.	EAN NO.
35	1872-35	6408487440977	47	1872-47	6408487441097
36	1872-36	6408487440984	48	1872-48	6408487441103
37	1872-37	6408487440991			
38	1872-38	6408487441004			
39	1872-39	6408487441011			
40	1872-40	6408487441028			
41	1872-41	6408487441035			
42	1872-42	6408487441042			
43	1872-43	6408487441059			
44	1872-44	6408487441066			
45	1872-45	6408487441073			
46	1872-46	6408487441080			

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## JALAS® 1872 OFF ROAD

### FEATURES

Wide fit, heat-resistant outsole, oil-resistant outsole, anti-static properties, bellows tongue, padded boot shaft, ventilating insole, pull loops, zipper, water repellent, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

### PREVENTS RISK OF

Antistatic

### PRIMARY ENVIRONMENTS OF USE

Outdoors, all-year use, harsh environments

2(3)



Heat-resistant outsole



Anti-static properties



Water repellent



ESD



Oil-resistant outsole



Wide fit



Ergothon Shock Absorption System



Zipper



Winter model

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-10-05

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

## JALAS® 1872 OFF ROAD

**COMPLIANCE**  
EN ISO 20347:2012

### COMPLIANCE DESCRIPTION

O1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + A + E

O2: O1 + WRU

WRU: Water-repellent upper

HRO: Heat-resistant outsole compound tested at 300°C

CI: Cold insulation

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

DGUV 112-191: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

Ö-Norm Z 1259: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



CE



Heat-resistant outsole



Anti-static properties



Water repellent



ESD



Oil-resistant outsole



Wide fit



Ergothon Shock Absorption System



Zipper



Winter model

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-10-05

3(3)

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com