



jalas[®]



JALAS[®] 1948 METATARSAL

EN ISO 20349:2010, S3, SRC, WG, HRO, M, CI, HI1, AI, Fe

PROPERTIES Highest level of protection, excellent grip, good fit, extra comfortable, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Outdoors, indoors, all-year use, warm surfaces, environments with risk for outsole penetration, oily and greasy environments, dirty environments, harsh environments

FEATURES ProNose toe reinforcement, wide fit, KEVLAR[®] thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit), heat-resistant upper, heat-resistant outsole, oil-resistant outsole, anti-static properties,

padded boot shaft, adjustable ankle strap, pull loops, water repellent, flame retardant, specially designed details, double shock absorption zones

UPPER MATERIAL Full-grain leather

SOLE MATERIAL PU midsole, plastic shank, rubber outsole

INSOLE FX2 Supreme

FITTING Wide

SIZE RANGE (EU) 36-48

CE



Aluminium toecap



ProNose toe reinforcement



Nail protection in plasma-treated composite (PTC) textile



Wide fit



Heat-resistant outsole



Ergothen Shock Absorption System



Water repellent



Heat-resistant upper



Oil-resistant outsole



Anti-static properties



jalas[®]



JALAS[®] 1948 METATARSAL

EN ISO 20349:2010, S3, SRC, WG, HRO, M, CI, HI1, AI, Fe

PROPERTIES Highest level of protection, excellent grip, good fit, extra comfortable, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Outdoors, indoors, all-year use, warm surfaces, environments with risk for outsole penetration, oily and greasy environments, dirty environments, harsh environments

FEATURES ProNose toe reinforcement, wide fit, KEVLAR[®] thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit), heat-resistant upper, heat-resistant outsole, oil-resistant outsole, anti-static properties,

padded boot shaft, adjustable ankle strap, pull loops, water repellent, flame retardant, specially designed details, double shock absorption zones

UPPER MATERIAL Full-grain leather

SOLE MATERIAL PU midsole, plastic shank, rubber outsole

INSOLE FX2 Supreme

FITTING Wide

SIZE RANGE (EU) 36-48

CE



Aluminium toecap



ProNose toe reinforcement



Nail protection in plasma-treated composite (PTC) textile



Wide fit



Heat-resistant outsole



Ergothen Shock Absorption System



Water repellent



Heat-resistant upper



Oil-resistant outsole



Anti-static properties