



### JALAS® 2102 RICHARD

EN ISO 20347:2012, O2, SRA, FO

PROPERTIES Good grip, perfect fit, extra comfortable, excellent shock absorption, light

PRIMARY ENVIRONMENTS OF USE Dry environments, clean environments

FEATURES Oil-resistant outsole, anti-static properties, ventilating insole, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

UPPER MATERIAL Full-grain leather

SOLE MATERIAL Plastic shank, PU outsole

INSOLE FX2 VIP Occupational

FITTING Regular

SIZE RANGE (EU) 39-47



Oil-resistant outsole



Anti-static properties



Ergothon Shock Absorption System



ESD



### JALAS® 2102 RICHARD

EN ISO 20347:2012, O2, SRA, FO

PROPERTIES Good grip, perfect fit, extra comfortable, excellent shock absorption, light

PRIMARY ENVIRONMENTS OF USE Dry environments, clean environments

FEATURES Oil-resistant outsole, anti-static properties, ventilating insole, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

UPPER MATERIAL Full-grain leather

SOLE MATERIAL Plastic shank, PU outsole

INSOLE FX2 VIP Occupational

FITTING Regular

SIZE RANGE (EU) 39-47



Oil-resistant outsole



Anti-static properties



Ergothon Shock Absorption System



ESD