

JALAS® 2108 VIP SAFETY

EN ISO 20345:2011, S3, SRA, HRO

PROPERTIES Good fit, comfortable, excellent shock absorption

SIZE RANGE (EU) 35-48



jalas®

www.jalas.com

JALAS® 2108 VIP SAFETY

EN ISO 20345:2011, S3, SRA, HRO

PROPERTIES Good fit, comfortable, excellent shock absorption

SIZE RANGE (EU) 35-48



jalas®

www.jalas.com

JALAS® 2108 VIP SAFETY

EN ISO 20345:2011, S3, SRA, HRO

PROPERTIES Good fit, comfortable, excellent shock absorption

SIZE RANGE (EU) 35-48



jalas®

www.jalas.com

JALAS® 2108 VIP SAFETY

EN ISO 20345:2011, S3, SRA, HRO

PROPERTIES Good fit, comfortable, excellent shock absorption

SIZE RANGE (EU) 35-48



jalas®

www.jalas.com

JALAS® 2108 VIP SAFETY

EN ISO 20345:2011, S3, SRA, HRO

PROPERTIES Good fit, comfortable, excellent shock absorption

SIZE RANGE (EU) 35-48



jalas®

www.jalas.com

JALAS® 2108 VIP SAFETY

EN ISO 20345:2011, S3, SRA, HRO

PROPERTIES Good fit, comfortable, excellent shock absorption

SIZE RANGE (EU) 35-48



jalas®

www.jalas.com

JALAS® 2108 VIP SAFETY

EN ISO 20345:2011, S3, SRA, HRO

PROPERTIES Good fit, comfortable, excellent shock absorption

SIZE RANGE (EU) 35-48



jalas®

www.jalas.com

JALAS® 2108 VIP SAFETY

EN ISO 20345:2011, S3, SRA, HRO

PROPERTIES Good fit, comfortable, excellent shock absorption

SIZE RANGE (EU) 35-48



jalas®

www.jalas.com

JALAS® 2108 VIP SAFETY

EN ISO 20345:2011, S3, SRA, HRO

PROPERTIES Good fit, comfortable, excellent shock absorption

SIZE RANGE (EU) 35-48



jalas®

www.jalas.com

JALAS® 2108 VIP SAFETY

EN ISO 20345:2011, S3, SRA, HRO

PROPERTIES Good fit, comfortable, excellent shock absorption

SIZE RANGE (EU) 35-48



jalas®

www.jalas.com