



### JALAS® 2108 VIP SAFETY

EN ISO 20345:2011, S3, SRA, HRO

PROPERTIES Good fit, comfortable, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Outdoors, indoors, office environments, all-year use, environments with risk for outsole penetration, dry environments, clean environments

FEATURES Anti-static properties, ventilating insole, water repellent leather, specially designed details, shock absorbing, conforms with IEC 61340-5-1 (ESD)

UPPER MATERIAL Full-grain leather

SOLE MATERIAL Rubber outsole

INSOLE FX2 VIP Safety

FITTING Narrow/Regular

SIZE RANGE (EU) 35-48



Steel toecap



Shock absorbing



Nail protection in plasma-treated composite (PTC) textile



Anti-static properties



Water repellent



ESD



Oil-resistant outsole



### JALAS® 2108 VIP SAFETY

EN ISO 20345:2011, S3, SRA, HRO

PROPERTIES Good fit, comfortable, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Outdoors, indoors, office environments, all-year use, environments with risk for outsole penetration, dry environments, clean environments

FEATURES Anti-static properties, ventilating insole, water repellent leather, specially designed details, shock absorbing, conforms with IEC 61340-5-1 (ESD)

UPPER MATERIAL Full-grain leather

SOLE MATERIAL Rubber outsole

INSOLE FX2 VIP Safety

FITTING Narrow/Regular

SIZE RANGE (EU) 35-48



Steel toecap



Shock absorbing



Nail protection in plasma-treated composite (PTC) textile



Anti-static properties



Water repellent



ESD



Oil-resistant outsole