

JALAS® 2108 VIP SAFETY

EN ISO 20345:2011, S3, SRA, HRO

PROPERTIES

Good fit, comfortable, excellent shock absorption

SPECIFICATION

TYPE OF SHOE Safety footwear, low shoes

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Narrow/Regular

SIZE RANGE (EU) 35-48

COLLECTION VIP Collection

UPPER MATERIAL Full-grain leather

UPPER MATERIAL THICKNESS 1,5-1,7

TOECAP MATERIAL Steel

LINING MATERIAL Leather

SOLE MATERIAL Rubber outsole

INSOLE FX2 VIP Safety

INSOLE MATERIAL Leather, soft EVA, polyester-based conductive thread, double shock absorption zones in Poron® XRD®

FASTENING Laces

COLOUR Black



SIZE	ART. NO.	EAN NO.	SIZE	ART. NO.	EAN NO.
35	2108B-35	6408487521706	47	2108B-47	6408487521614
36	2108B-36	6408487521171	48	2108B-48	6408487521652
37	2108B-37	6408487521218			
38	2108B-38	6408487521256			
39	2108B-39	6408487521294			
40	2108B-40	6408487521331			
41	2108B-41	6408487521379			
42	2108B-42	6408487521416			
43	2108B-43	6408487521454			
44	2108B-44	6408487521492			
45	2108B-45	6408487521539			
46	2108B-46	6408487521577			

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

JALAS® 2108 VIP

SAFETY

FEATURES

Anti-static properties, ventilating insole, water repellent leather, specially designed details, shock absorbing, conforms with IEC 61340-5-1 (ESD)

PREVENTS RISK OF

Prevents risk of: toe injuries, nail penetration, sprain injuries, antistatic, slipping, strain injuries

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, office environments, all-year use, environments with risk for outsole penetration, dry environments, clean environments

PRIMARY AREAS OF USE

Engineering, office work

2(3)



Steel toecap



Nail protection in plasma-treated composite (PTC) textile



Water repellent



Oil-resistant outsole



Shock absorbing



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-10-05

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

JALAS® 2108 VIP SAFETY

COMPLIANCE
EN ISO 20345:2011

COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S1P: S1+P

S2: S1 + WRU

S3: S2 + P

WRU: Water-repellent upper

P: Penetration-resistant outsole

HRO: Heat-resistant outsole compound tested at 300°C

FO: Oil-resistant outsole

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

ESD: Electro Static Discharge

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

DGUV 112-191: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

Ö-Norm Z 1259: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



Steel toecap



Nail protection in plasma-treated composite (PTC) textile



Water repellent



Oil-resistant outsole



Shock absorbing



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-10-05

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com