

JALAS® 2128 VIP SAFETY

EN ISO 20345:2011, S3, SRA, HRO

PROPERTIES

Good fit, comfortable, excellent shock absorption

SPECIFICATION

TYPE OF SHOE Safety footwear, boots/Ankle boots

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Narrow/Regular

SIZE RANGE (EU) 35-48

COLLECTION VIP Collection

UPPER MATERIAL Full-grain leather

UPPER MATERIAL THICKNESS 1.6-1.8

TOECAP MATERIAL Steel

SOLE MATERIAL Rubber outsole

INSOLE FX2 VIP Safety

INSOLE MATERIAL Leather, soft EVA, polyester-based conductive thread, double shock absorption zones in Poron® XRD®

FASTENING Laces

COLOUR Brown



SIZE	ART. NO.	EAN NO.	SIZE	ART. NO.	EAN NO.
35	2128-35	6408487509698	47	2128-47	6408487509810
36	2128-36	6408487509704	48	2128-48	6408487509827
37	2128-37	6408487509711			
38	2128-38	6408487509728			
39	2128-39	6408487509735			
40	2128-40	6408487509742			
41	2128-41	6408487509759			
42	2128-42	6408487509766			
43	2128-43	6408487509773			
44	2128-44	6408487509780			
45	2128-45	6408487509797			
46	2128-46	6408487509803			

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

JALAS® 2128 VIP SAFETY

FEATURES

Anti-static properties, ventilating insole, water repellent leather, specially designed details, shock absorbing, conforms with IEC 61340-5-1 (ESD)

PREVENTS RISK OF

Prevents risk of: toe injuries, nail penetration, sprain injuries, antistatic, strain injuries

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, office environments, environments with risk for outsole penetration, dry environments, clean environments

PRIMARY AREAS OF USE

Engineering, office work



Steel toecap



Nail protection in plasma-treated composite (PTC) textile



Water repellent



Oil-resistant outsole



Shock absorbing



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-05-09

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

JALAS® 2128 VIP SAFETY

COMPLIANCE
EN ISO 20345:2011

COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S1P: S1+P

S2: S1 + WRU

S3: S2 + P

WRU: Water-repellent upper

P: Penetration-resistant outsole

FO: Oil-resistant outsole

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

DGUV 112-191: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

Ö-Norm Z 1259: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



CE



Steel toecap



Nail protection in plasma-treated composite (PTC) textile



Water repellent



Oil-resistant outsole



Shock absorbing



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-05-09

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com