



STREET 3075

EN ISO 20345:2011 S3, SRC



[Learn more](#)

LIGHT MID CUT LEATHER SHOE

A good looking and sporty comfortable mid cut safety boot with perfect fit and classic look. It has the highest level of protection with aluminium toecap and nail protection in plasma treated composite textile. The boot has an excellent shock absorbing system (Ergothan) which makes it comfortable to use a hole working day. Oil resistant outsole, ESD protection. The mid cut provides extra ankle support.

CHARACTERISTICS

- Excellent grip
- Perfect fit
- Extra comfortable
- Excellent shock absorption

FUNCTIONS

- Anti-static properties
- Soft
- Ventilating insole
- Conforms with IEC 61340-5-1 (ESD)
- Polstered shaft edge



PREVENTS RISK OF

Toe injuries, nail penetration, antistatic, slipping

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, office environments, all-year use, environments with risk for outsole penetration, dry environments, clean environments, environments with explosive risks

PRIMARY AREAS OF USE

Assembly, building and construction, carpentry, electrical installation, engineering, fine assembly, hvac installation, inspection work, installation work, laboratory work, machine driving, machine operating, marine work, paint spraying work, painting, paper industry work, repair work, service work, transport work, warehouse work, wood industry work

PRIMARY INDUSTRIES OF USE

Automotive, transportation, utilities, building and construction, logistics, facilities, service, retail

SPECIFICATION

TYPE Safety footwear, Boots/Ankle boots

CATEGORY Cat. II

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Regular

COLLECTION Street

UPPER MATERIAL Split leather, Textile

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyamide

INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Double shock absorption zones in Poron® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL RPU outsole

FASTENING Laces

SHOELACES LENGTH 145 cm

COLOUR Black, Red, White

NET WEIGHT, (SIZE 42) 1.16 kg

COMPLIANCE



TP TC 019:2011



EN ISO 20345:2011 S3, SRC



ÖNORM Z 1259



FEATURES



Oil-resistant outsole



Aluminium toecap



Nail protection in plasma-treated composite (PTC) textile



Anti-static properties



ESD



Ergothon Shock Absorption System



Stabilizator

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
35	2	3½	4	3075-35	6408487521072
36	3	4	5	3075-36	6408487502934
37	4	5	6	3075-37	6408487502941
38	5	5½	6½	3075-38	6408487502958
39	6	6½	7½	3075-39	6408487502965
40	6½	7½	8½	3075-40	6408487502972
41	7	8	9	3075-41	6408487502989
42	8	9	10	3075-42	6408487502996
43	9	9½	11	3075-43	6408487503009
44	10	10½	11½	3075-44	6408487503016
45	10½	11	12½	3075-45	6408487503023
46	11	12	13	3075-46	6408487503030
47	12	13	14	3075-47	6408487503047
48	13	13½	14½	3075-48	6408487521119

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com