



## JALAS® 3318 DRYLOCK

EN ISO 20345:2011, S3, SRB, WR, HRO

**PROPERTIES** Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

**PRIMARY ENVIRONMENTS OF USE** Outdoors, all-year use, environments with risk for outsole penetration, wet environments, harsh environments

**FEATURES** Waterproof Drylock-membrane, ProNose toe reinforcement, heat-resistant outsole, oil-resistant outsole, anti-static properties, bellows tongue, padded boot shaft, ventilating insole, quick-tie, waterproof, reflector, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

**UPPER MATERIAL** Cordura®, Full-grain leather

**SOLE MATERIAL** PU midsole, rubber outsole

**INSOLE** FX2 Supreme

**FITTING** Regular

**SIZE RANGE (EU)** 36-47



Aluminium toecap



ProNose toe reinforcement



Nail protection in steel



Ergo Shock Absorption System



Heat-resistant outsole



Anti-static properties



Waterproof



ESD



Oil-resistant outsole



## JALAS® 3318 DRYLOCK

EN ISO 20345:2011, S3, SRB, WR, HRO

**PROPERTIES** Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

**PRIMARY ENVIRONMENTS OF USE** Outdoors, all-year use, environments with risk for outsole penetration, wet environments, harsh environments

**FEATURES** Waterproof Drylock-membrane, ProNose toe reinforcement, heat-resistant outsole, oil-resistant outsole, anti-static properties, bellows tongue, padded boot shaft, ventilating insole, quick-tie, waterproof, reflector, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

**UPPER MATERIAL** Cordura®, Full-grain leather

**SOLE MATERIAL** PU midsole, rubber outsole

**INSOLE** FX2 Supreme

**FITTING** Regular

**SIZE RANGE (EU)** 36-47



Aluminium toecap



ProNose toe reinforcement



Nail protection in steel



Ergo Shock Absorption System



Heat-resistant outsole



Anti-static properties



Waterproof



ESD



Oil-resistant outsole