

## JALAS® 3318 DRYLOCK

EN ISO 20345:2011, S3, SRB, WR, HRO

### PROPERTIES

Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

### SPECIFICATION

TYPE OF SHOE Safety footwear, boots/Ankle boots

NAIL PROTECTION MATERIAL Steel

FITTING Regular

SIZE RANGE (EU) 36-47

COLLECTION Drylock

PLATFORM Grip

UPPER MATERIAL Cordura®, Full-grain leather

SHOEPRONOSEMATERIAL PU

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester, polyamide, Drylock membrane

SOLEMATERIAL PU midsole, rubber outsole

INSOLE FX2 Supreme

INSOLE MATERIAL Textile, soft EVA, polyester-based conductive thread, Merino wool, double shock absorption zones in Poron® XRD®

FASTENING Laces

COLOUR Black, Grey, Red



**DRY+LOCK**

SIZE	ART. NO.	EAN NO.
36	3318-36	6408487427947
37	3318-37	6408487427954
38	3318-38	6408487427961
39	3318-39	6408487427978
40	3318-40	6408487427985
41	3318-41	6408487427992
42	3318-42	6408487428005
43	3318-43	6408487428012
44	3318-44	6408487428029
45	3318-45	6408487428036
46	3318-46	6408487428043
47	3318-47	6408487428050

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## JALAS® 3318 DRYLOCK

### FEATURES

Waterproof Drylock-membrane, ProNose toe reinforcement, heat-resistant outsole, oil-resistant outsole, anti-static properties, bellows tongue, padded boot shaft, ventilating insole, quick-tie, waterproof, reflector, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

### PREVENTS RISK OF

Toe injuries, nail penetration, antistatic, wet feet

### PRIMARY ENVIRONMENTS OF USE

Outdoors, all-year use, environments with risk for outsole penetration, wet environments, harsh environments



CE



Aluminium toecap



Anti-static properties



Nail protection in steel



ESD



Heat-resistant outsole



Waterproof



Oil-resistant outsole



ProNose toe reinforcement



Ergothon Shock Absorption System

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-05-09

2(3)

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

## JALAS® 3318 DRYLOCK

**COMPLIANCE**  
EN ISO 20345:2011

### COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S2: S1 + WRU

S3: S2 + P

WR: Water-resistant footwear

WRU: Water-repellent upper

P: Penetration-resistant outsole

HRO: Heat-resistant outsole compound tested at 300°C

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRB: Slip-resistance on steel floor with glycerol

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

DGUV 112-191: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

Ö-Norm Z 1259: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



CE



Aluminium toecap



Anti-static properties



Nail protection in steel



ESD



Heat-resistant outsole



Waterproof



Oil-resistant outsole



ProNose toe reinforcement



Ergothon Shock Absorption System

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-05-09

3(3)

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com