



jalas[®] RESPIRO 3700R

EN ISO 20345:2011 S2, SRB



Learn more

Toecap material aluminium, PU midsole, plastic shank, TPU outsole, upper material nubuck leather;PU-coated leather;Textile

CHARACTERISTICS

- Excellent shock absorption
- Good grip
- Perfect fit
- Extra comfortable
- Very breathable

FUNCTIONS

- Oil-resistant outsole
- Anti-static properties
- Stabilizator
- Water repellent
- Polstered shaft edge
- Conforms with IEC 61340-5-1 (ESD)
- Double shock absorption zones
- Ultra-high air permeability, three-layer laminate, 'provided by IQTEX based on patented technologies'
- Perforated
- Perforated front section



PREVENTS RISK OF

Toe injuries, antistatic

PRIMARY ENVIRONMENTS OF USE

Indoors, dry environments, clean environments

SPECIFICATION

TYPE Safety footwear, Low shoes

CATEGORY Cat. II

FITTING Regular

COLLECTION Respiro

UPPER MATERIAL PU-coated leather, Nubuck leather, Textile

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester, polyamide

INSOLE FX2 Climate

INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Merino wool, Double shock absorption zones in Poron® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL TPU outsole

FASTENING Laces

SHOELACES LENGTH 90 cm

COLOUR Black, Red, Blue

NET WEIGHT, (SIZE 42) 0.97 kg

COMPLIANCE



TP TC 019:2011

EN ISO 20345:2011
S2, SRB



ÖNORM Z 1259



DGVV 112-191

FEATURES



Anti-static properties



Ergothan Shock Absorption System



ESD



Aluminium toecap



Oil-resistant outsole



Water repellent



Stabilizator

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
36	3	4	5	3700R-36	6408487504631
37	4	5	6	3700R-37	6408487504648
38	5	5½	6½	3700R-38	6408487504655
39	6	6½	7½	3700R-39	6408487504662
40	6½	7½	8½	3700R-40	6408487504679
41	7	8	9	3700R-41	6408487504686
42	8	9	10	3700R-42	6408487504693
43	9	9½	11	3700R-43	6408487504709
44	10	10½	11½	3700R-44	6408487504716
45	10½	11	12½	3700R-45	6408487504723
46	11	12	13	3700R-46	6408487504730
47	12	13	14	3700R-47	6408487504747

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com