



jalas® RESPIRO 3820R

EN ISO 20345:2011 S1, SRB



[Learn more](#)

Toecap material aluminium, PU midsole, plastic shank, TPU outsole, upper material nubuck leather, Textile

CHARACTERISTICS

- Excellent shock absorption
- Good grip
- Perfect fit
- Extra comfortable
- Very breathable

FUNCTIONS

- Oil-resistant outsole
- Anti-static properties
- Double shock absorption zones
- Stabilizer
- Polstered shaft edge
- Conforms with IEC 61340-5-1 (ESD)
- Ultra-high air permeability, three-layer laminate, 'provided by IQTEX based on patented technologies'
- Perforated
- Perforated front section



PREVENTS RISK OF

Toe injuries, antistatic

PRIMARY ENVIRONMENTS OF USE

Indoors, dry environments, clean environments

SPECIFICATION

TYPE Safety footwear, Sandals

CATEGORY Cat. II

FITTING Regular

COLLECTION Respiro

UPPER MATERIAL Nubuck leather, Textile

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester, polyamide

INSOLE JALAS 8217 FX2 Climate

INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Merino wool, Double shock absorption zones in Poron® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL TPU outsole

FASTENING Hook-and-loop

COLOUR Black, Red, Blue

NET WEIGHT, (SIZE 42) 1,04 kg

COMPLIANCE



TP TC 019:2011

EN ISO 20345:2011
S1, SRB



ÖNORM Z 1259



DGVU 112-191

FEATURES



Anti-static properties



Ergothon Shock Absorption System



ESD



Aluminium toecap



Oil-resistant outsole



Stabilizator

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
36	3	4	5	3820R-36	6408487505805
37	4	5	6	3820R-37	6408487505812
38	5	5.5	6.5	3820R-38	6408487505829
39	6	6.5	7.5	3820R-39	6408487505836
40	6.5	7.5	8.5	3820R-40	6408487505843
41	7	8	9	3820R-41	6408487505850
42	8	9	10	3820R-42	6408487505867
43	9	9.5	11	3820R-43	6408487505874
44	10	10.5	11.5	3820R-44	6408487505881
45	10.5	11	12.5	3820R-45	6408487505898
46	11	12	13	3820R-46	6408487505904
47	12	13	14	3820R-47	6408487505911

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com