

JALAS® 3920A CHALLENGER

EN ISO 20345:2011, S1, SRB, HRO

PROPERTIES

Highest level of protection, excellent grip, perfect fit, extra comfortable, breathable, excellent shock absorption

SPECIFICATION

TYPE OF SHOE Safety footwear, sandals

FITTING Regular

SIZE RANGE (EU) 36-47

COLLECTION Grip

PLATFORM Grip

UPPER MATERIAL Nubuck leather, Textile

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester, polyamide

SOLE MATERIAL PU midsole, plastic shank, rubber outsole

INSOLE FX2 Supreme

INSOLE MATERIAL Textile, soft EVA, polyester-based conductive thread, Merino wool, double shock absorption zones in Poron® XRD®

FASTENING Hook-and-loop

COLOUR Black, Grey



SIZE	ART. NO.	EAN NO.
36	3920A-36	6408487425264
37	3920A-37	6408487425271
38	3920A-38	6408487425288
39	3920A-39	6408487425295
40	3920A-40	6408487425301
41	3920A-41	6408487425318
42	3920A-42	6408487425325
43	3920A-43	6408487425332
44	3920A-44	6408487425349
45	3920A-45	6408487425356
46	3920A-46	6408487425363
47	3920A-47	6408487425370

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



JALAS® 3920A CHALLENGER

FEATURES

Heat-resistant outsole, oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, adjustable heel strap, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

PREVENTS RISK OF

Toe injuries, antistatic

PRIMARY ENVIRONMENTS OF USE

Indoors

2(3)



Aluminium toecap



Heat-resistant outsole



Oil-resistant outsole



Ergothon Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-06-16

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

JALAS® 3920A CHALLENGER

COMPLIANCE
EN ISO 20345:2011

COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

HRO: Heat-resistant outsole compound tested at 300°C

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRB: Slip-resistance on steel floor with glycerol

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

DGUV 112-191: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

Ö-Norm Z 1259: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



Aluminium toecap



Heat-resistant outsole



Oil-resistant outsole



Ergothon Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-06-16

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com