

JALAS® 3941 HUNTER

EN ISO 20345:2011, S2, SRB, HRO

PROPERTIES

Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

SPECIFICATION

TYPE OF SHOE Safety footwear, boots/Ankle boots

FITTING Regular

SIZE RANGE (EU) 36-47

COLLECTION Grip

PLATFORM Grip

UPPER MATERIAL PU-coated leather

SHOEPRONOSEMATERIAL PU

TOECAP MATERIAL Aluminium

LINING MATERIAL Cambrelle®, polyamide

SOLEMATERIAL PU midsole, plastic shank, rubber outsole

INSOLE FX2 Pro

INSOLE MATERIAL Textile, soft EVA, polyester-based conductive thread, double shock absorption zones in Poron® XRD®

FASTENING Zipper

COLOUR Black, Yellow



| SIZE | ART. NO. | EAN NO. |
|------|----------|---------------|
| 36 | 3941-36 | 6408487390357 |
| 37 | 3941-37 | 6408487390364 |
| 38 | 3941-38 | 6408487390371 |
| 39 | 3941-39 | 6408487390388 |
| 40 | 3941-40 | 6408487390395 |
| 41 | 3941-41 | 6408487390401 |
| 42 | 3941-42 | 6408487390418 |
| 43 | 3941-43 | 6408487390425 |
| 44 | 3941-44 | 6408487390432 |
| 45 | 3941-45 | 6408487390449 |
| 46 | 3941-46 | 6408487390456 |
| 47 | 3941-47 | 6408487390463 |

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

JALAS® 3941 HUNTER

FEATURES

ProNose toe reinforcement, KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit), heat-resistant upper, heat-resistant outsole, oil-resistant outsole, anti-static properties, padded boot shaft, ventilating insole, pull loops, zipper, water repellent, double shock absorption zones, conforms with IEC 61340-5-1 (ESD), heat-resistant, withstands welding sparks and grinding splash

PREVENTS RISK OF

Toe injuries, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, warm surfaces, harsh environments

PRIMARY AREAS OF USE

Hot work, metalwork, sheet-metal work, welding

PRIMARY INDUSTRIES OF USE

Metal fabrication



Aluminium toecap



Zipper



Heat-resistant outsole



Anti-static properties



Water repellent



ESD



Oil-resistant outsole



ProNose toe reinforcement



Ergothan Shock Absorption System



Heat-resistant upper

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-05-09

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

JALAS® 3941 HUNTER

COMPLIANCE
EN ISO 20345:2011

COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S2: S1 + WRU

WRU: Water-repellent upper

HRO: Heat-resistant outsole compound tested at 300°C

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRB: Slip-resistance on steel floor with glycerol

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

DGUV 112-191: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

Ö-Norm Z 1259: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



CE



Aluminium toecap



Zipper



Heat-resistant outsole



Anti-static properties



Water repellent



ESD



Oil-resistant outsole



ProNose toe reinforcement



ErgoShock Absorption System



Heat-resistant upper

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-05-09

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com