TEGERA®





Learn more

TEGERA® 431

HIGH DURABILITY WITH GOOD GRIP

A versatile cut protection glove with CRF° technology and high durability as it has a double dipped palm in nitrile. Sandy finish provides good grip in damp and slightly oily environments. Withstands contact heat up to $100\,^{\circ}\text{C}/212\,^{\circ}\text{F}$. Suitable for assembly work and metal work, among other things.

CHARACTERISTICS

- Very durable
- Good grip

FUNCTIONS

- Withstands contact heat up to 100°C
- Oil and grease resistant palm



PREVENTS RISK OF

PRIMARY ENVIRONMENTS OF USE

Cut risk environments, dry environments, oily and greasy environments, dirty environments

PRIMARY AREAS OF USE

Assembly, machine operating, building and construction, engineering, transport work, metalwork

PRIMARY INDUSTRIES OF USE

Agriculture, mining, metal fabrication, machinery and equipment, mro, automotive, building and construction

TYPE OF WORK

Medium weight

SPECIFICATION

TYPE Cut resistant gloves, Heat protection gloves

CATEGORY Cat. II

LINING MATERIAL 13 gg, CRF® Technology, HPPE, Nylon, Spandex

LENGTH 210-280 mm

DEXTERITY 5

GRIP DESIGN Sandy finish

COLOUR Grey, Black

PAIRS PER: BUNDLE/CARTON 12/60

DISPLAY TYPE Bulk pack

DIPPING Palm-dipped, Double-dipped

DIPPING MATERIAL Nitrile, Nitrile foam

CUFF STYLE Knitwrist cuff

CUFF MATERIAL Textile

CUT RESISTANCE (EN ISO 13997) Cut resistance level B

CUT RESISTANCE (EN ISO 13997) TDM: 5.4 N

INNER MATERIAL SPECIFICATION HPPE (High performance

polyethylene), Nylon, Elastane

OUTER MATERIAL SPECIFICATION Nitrile

COMPLIANCE







TP TC 019:2011







EN 388:2016+A1:2018 4X43B

EN ISO 21420:2020 5+41-2018







Contact heat rating valid for palm area only

FEATURES



SIZE		ARTICLE NUMBER	EAN
5	XXS	431-5	7340118355870
6	XS	431-6	7340118322438
7	S	431-7	7340118322445
8	М	431-8	7340118322452
9	L	431-9	7340118322469
10	XL	431-10	7340118322407
11	XXL	431-11	7340118322414
12	3XL	431-12	7340118322421



Limavägen 28, SE-793 32 Leksand, Sweden Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com