



JALAS® 4768 FIRE +

EN 15090:2012, SRA, CI

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Outdoors, all-year use, environments with risk for outsole penetration, wet environments, harsh environments

FEATURES D30® impact protection zone, KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit), heat-resistant upper, heat-resistant outsole, oil-resistant outsole, anti-static properties, padded boot shaft, ventilating insole, pull loops, waterproof, reflector, specially designed details, double shock

absorption zones, heat-resistant, withstands welding sparks and grinding splash

UPPER MATERIAL PU-coated leather

SOLE MATERIAL Solid rubber outsole

INSOLE FX2 Pro

FITTING Regular

SIZE RANGE (EU) 39-48

jalas®



CE



Aluminium toecap



Oil-resistant outsole



Nail protection in steel



Ergo-Shock Absorption System



Heat-resistant outsole



Heat-resistant upper



Waterproof



Anti-static properties



JALAS® 4768 FIRE +

EN 15090:2012, SRA, CI

PROPERTIES Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

PRIMARY ENVIRONMENTS OF USE Outdoors, all-year use, environments with risk for outsole penetration, wet environments, harsh environments

FEATURES D30® impact protection zone, KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit), heat-resistant upper, heat-resistant outsole, oil-resistant outsole, anti-static properties, padded boot shaft, ventilating insole, pull loops, waterproof, reflector, specially designed details, double shock

absorption zones, heat-resistant, withstands welding sparks and grinding splash

UPPER MATERIAL PU-coated leather

SOLE MATERIAL Solid rubber outsole

INSOLE FX2 Pro

FITTING Regular

SIZE RANGE (EU) 39-48

jalas®



CE



Aluminium toecap



Oil-resistant outsole



Nail protection in steel



Ergo-Shock Absorption System



Heat-resistant outsole



Heat-resistant upper



Waterproof



Anti-static properties