

JALAS® 5012 MENU WHITE

EN ISO 20347:2012, 01, SRC

PROPERTIES

Excellent grip, good fit, comfortable, breathable, excellent shock absorption, light

SPECIFICATION

TYPE OF SHOE Occupational footwear, sandals

FITTING Regular

SIZE RANGE (EU) 36-47

COLLECTION Grand Walking

PLATFORM Grand Walking

UPPER MATERIAL Microfiber

LINING MATERIAL Polyester, polyamide

SOLE MATERIAL Plastic shank, PU outsole

INSOLE FX2 Pro

INSOLE MATERIAL Textile, soft EVA, polyester-based conductive thread, double shock absorption zones in Poron® XRD®

FASTENING Hook-and-loop

COLOUR White



GRAND WALKING

| SIZE | ART. NO. | EAN NO. |
|------|----------|---------------|
| 36 | 5012-36 | 6408487418976 |
| 37 | 5012-37 | 6408487418983 |
| 38 | 5012-38 | 6408487418990 |
| 39 | 5012-39 | 6408487419003 |
| 40 | 5012-40 | 6408487419010 |
| 41 | 5012-41 | 6408487419027 |
| 42 | 5012-42 | 6408487419034 |
| 43 | 5012-43 | 6408487419041 |
| 44 | 5012-44 | 6408487419058 |
| 45 | 5012-45 | 6408487419065 |
| 46 | 5012-46 | 6408487419072 |
| 47 | 5012-47 | 6408487419089 |

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



JALAS® 5012 MENU WHITE

FEATURES

Low weight, oil-resistant outsole, adjustable heel strap, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

PREVENTS RISK OF

Antistatic, slipping

PRIMARY ENVIRONMENTS OF USE

Indoors, slippery environments, dry environments

PRIMARY AREAS OF USE

Cleaning, healthcare, hotel- and restaurant work, kitchen work, shop work

PRIMARY INDUSTRIES OF USE

HoReCa, service

2(3)



Oil-resistant outsole



Ergo-Shock Absorption System



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-06-16

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

JALAS® 5012 MENU WHITE

COMPLIANCE
EN ISO 20347:2012

COMPLIANCE DESCRIPTION

O1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + A + E

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm



Oil-resistant outsole



Ergothon Shock Absorption System



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-06-16

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com