

## JALAS® 5362 SPOC

EN ISO 20347:2012, 01, SRC, FO, A, E

### PROPERTIES

Excellent grip, perfect fit, extra comfortable, breathable, excellent shock absorption, light

### SPECIFICATION

TYPE OF SHOE Occupational footwear, low shoes

FITTING Regular

SIZE RANGE (EU) 35-48

COLLECTION Sp0c

PLATFORM Active

UPPER MATERIAL Textile

LINING MATERIAL Polyester

SOLE MATERIAL EVA, rubber outsole

INSOLE FX2 PRO Sp0c

INSOLE MATERIAL Textile, soft EVA, polyester-based conductive thread, double shock absorption zones in Poron® XRD®

FASTENING BOA® Fit System

COLOUR Black, Orange



**SPOC**  
COLLECTION

SIZE	ART. NO.	EAN NO.	SIZE	ART. NO.	EAN NO.
35	5362-35	6408487510465	47	5362-47	6408487510588
36	5362-36	6408487510472	48	5362-48	6408487510595
37	5362-37	6408487510489			
38	5362-38	6408487510496			
39	5362-39	6408487510502			
40	5362-40	6408487510519			
41	5362-41	6408487510526			
42	5362-42	6408487510533			
43	5362-43	6408487510540			
44	5362-44	6408487510557			
45	5362-45	6408487510564			
46	5362-46	6408487510571			

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



## JALAS® 5362 SPOC

### FEATURES

Breathable mesh, low weight, oil-resistant outsole, anti-static properties, BOA® Fit System, ESD, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

### PREVENTS RISK OF

Prevents risk of: sprain injuries, antistatic, slipping, strain injuries

### PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, office environments, slippery environments

### PRIMARY AREAS OF USE

Care work, cleaning, healthcare, hotel- and restaurant work, office work, service work, shop work

### PRIMARY INDUSTRIES OF USE

HoReCa, facilities, service, retail



Oil-resistant outsole



Ergo-Shock Absorption System



Anti-static properties



ESD

*The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.*

2021-08-24

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

## JALAS® 5362 SPOC

**COMPLIANCE**  
EN ISO 20347:2012

### COMPLIANCE DESCRIPTION

O1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + A + E

FO: Oil-resistant outsole

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

DGUV 112-191: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

Ö-Norm Z 1259: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



CE



Oil-resistant outsole



Ergothon Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-08-24

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com