

JALAS® 7118 ZENIT EVO

EN ISO 20345:2011, S1, P, SRC

PROPERTIES

Excellent grip, perfect fit, extra comfortable, very breathable, excellent shock absorption, extremely light

SPECIFICATION

TYPE OF SHOE Safety footwear, low shoes

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Regular

SIZE RANGE (EU) 35-48

COLLECTION Zenit Evo

PLATFORM Custom

UPPER MATERIAL Textile

UPPER MATERIAL THICKNESS 1,8-2,0

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester

SOLE MATERIAL PU midsole, plastic shank, RPU outsole

INSOLE FX3 Supreme

INSOLE MATERIAL Textile, soft EVA, rigid EVA, polyester-based conductive thread, neo foam, double shock absorption zones in Poron® XRD®

FASTENING BOA® Fit System

COLOUR Black, Grey, White



ZENIT EVO
COLLECTION



SIZE	ART. NO.	EAN NO.	SIZE	ART. NO.	EAN NO.
35	7118-35	6408487507915	47	7118-47	6408487508035
36	7118-36	6408487507922	48	7118-48	6408487508042
37	7118-37	6408487507939			
38	7118-38	6408487507946			
39	7118-39	6408487507953			
40	7118-40	6408487507960			
41	7118-41	6408487507977			
42	7118-42	6408487507984			
43	7118-43	6408487507991			
44	7118-44	6408487508004			
45	7118-45	6408487508011			
46	7118-46	6408487508028			

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

JALAS® 7118 ZENIT EVO

FEATURES

Low weight, oil-resistant outsole, anti-static properties, bellows tongue, padded shaft edge in memory foam, ventilating insole, BOA® Fit System, ergonomically shaped, conforms with IEC 61340-5-1 (ESD)

PREVENTS RISK OF

Toe injuries, nail penetration, antistatic, slipping

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, environments with risk for outsole penetration, dry environments, clean environments



CE



Aluminium toecap



Nail protection in plasma-treated composite (PTC) textile



Oil-resistant outsole



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-05-09

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

JALAS® 7118 ZENIT EVO

COMPLIANCE
EN ISO 20345:2011

COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S1P: S1+P

P: Penetration-resistant outsole

FO: Oil-resistant outsole

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

DGUV 112-191: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

Ö-Norm Z 1259: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



CE



Aluminium toecap



Nail protection in plasma-treated composite (PTC) textile



Oil-resistant outsole



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-05-09

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com