



TEGERA® 7390



[Learn more](#)

TRIPLE DIPPED WINTER SHIELD GLOVE

Triple-dipped shield glove designed for those who perform heavy work in extremely cold conditions involving exposure to chemicals or oil. It features a seamless, soft winter lining in fleece for good comfort and is made of 0.4 mm/15,7 mil PVC (Vinyl). Comfortable, durable, and waterproof.

CHARACTERISTICS

- Good fit
- Flexible
- Very durable
- Warm
- Good grip
- Comfortable

FUNCTIONS

- Waterproof
- Protection against chemicals
- Oil and grease resistant

PREVENTS RISK OF

Corrosive injuries, contact with dirt, contact with chemicals, contact with damp, contact with oil, contact with cold

PRIMARY ENVIRONMENTS OF USE

Chemical risk environments, environments hazardous to health, corrosive environments, outdoors, moist environments, oily and greasy environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Agricultural work, airport work, building and construction, chemical technology work, chemical work, concrete work, construction, fishing industry work, hvac installation, machine operating, mining, soil preparation

PRIMARY INDUSTRIES OF USE

Agriculture, mining, oil, gas, petrochemical, chemical

TYPE OF WORK

Heavy weight

CHEMICAL RESISTANCE

According to EN16523-1:2015. For details, please contact Ejendals.

SPECIFICATION

TYPE Chemical protection gloves, Cold insulation gloves

CATEGORY Cat. III

THICKNESS 0,4* mm (*chem-layer)

LINING Winter-lined

LINING MATERIAL Fleece, Acrylic

LENGTH 300 mm

DEXTERITY 4

GRIP DESIGN Sandy finish

COLOUR Blue

PAIRS PER: BUNDLE/CARTON 6/36

AQL 0.65

DISPLAY TYPE Bulk pack


DIPPING Fully dipped

DIPPING MATERIAL PVC (Vinyl)



COMPLIANCE




TP TC 019:2011



EN ISO 374-1:2016/A1:2018 Type A
AKLMNOPT




EN ISO 21420:2020



EN 511 cl. 5.2 Flexibility behavior (-20°C)

EN 511 cl. 5.4 Extreme cold flexibility (-50°C)

FEATURES



TEST ACCORDING TO EN ISO 374-1:2016

| Tested chemical | A | K | L | M | N | O | P | T |
|------------------|------|------|-----|------|-----|------|-----|------|
| Permeation level | 3 | 6 | 4 | 5 | 2 | 2 | 6 | 6 |
| Degradation % | -9,1 | -7,3 | 2,7 | 50,1 | 9,8 | 20,3 | 3,2 | -4,0 |

| SIZE | | ARTICLE NUMBER | EAN |
|------|----|----------------|---------------|
| 9 | L | 7390-9 | 7392626075221 |
| 10 | XL | 7390-10 | 7392626008311 |

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com