TEGERA® 7798

Leather glove, winter-lined, full grain goatskin of top quality, spandex, fleece, Thinsulate™ 40g, Cat. II, black, yellow, reinforced index finger, high visibility colour, for touchscreen, waterproof, reflector, for allround work

PROPERTIES Flexible, durable, excellent grip, perfect fit, extra comfortable

CE Cat. II EN 420:2003 + A1:2009 | EN 388:2016 2111X | EN 511:2006 111

EN ISO 11640:2012
Dry 150 cycles 4/5 Wet 50 cycles 3/4

www.ejendals.com

TEGERA® 7798

Leather glove, winter-lined, full grain goatskin of top quality, spandex, fleece, Thinsulate™ 40g, Cat. II, black, yellow, reinforced index finger, high visibility colour, for touchscreen, waterproof, reflector, for allround work

PROPERTIES Flexible, durable, excellent grip, perfect fit, extra comfortable

CE Cat. II EN 420:2003 + A1:2009 | EN 388:2016 2111X | EN 511:2006 111

EN ISO 11640:2012
Dry 150 cycles 4/5 Wet 50 cycles 3/4

www.ejendals.com

TEGERA® 7798

Leather glove, winter-lined, full grain goatskin of top quality, spandex, fleece, Thinsulate™ 40g, Cat. II, black, yellow, reinforced index finger, high visibility colour, for touchscreen, waterproof, reflector, for allround work

PROPERTIES Flexible, durable, excellent grip, perfect fit, extra comfortable

CE Cat. II EN 420:2003 + A1:2009 | EN 388:2016 2111X | EN 511:2006 111

EN ISO 11640:2012
Dry 150 cycles 4/5 Wet 50 cycles 3/4

www.ejendals.com

TEGERA® 7798

Leather glove, winter-lined, full grain goatskin of top quality, spandex, fleece, Thinsulate™ 40g, Cat. II, black, yellow, reinforced index finger, high visibility colour, for touchscreen, waterproof, reflector, for allround work

PROPERTIES Flexible, durable, excellent grip, perfect fit, extra comfortable

CE Cat. II EN 420:2003 + A1:2009 | EN 388:2016 2111X | EN 511:2006 111

EN ISO 11640:2012
Dry 150 cycles 4/5 Wet 50 cycles 3/4

www.ejendals.com

TEGERA® 7798

Leather glove, winter-lined, full grain goatskin of top quality, spandex, fleece, Thinsulate™ 40g, Cat. II, black, yellow, reinforced index finger, high visibility colour, for touchscreen, waterproof, reflector, for allround work

PROPERTIES Flexible, durable, excellent grip, perfect fit, extra comfortable

CE Cat. II EN 420:2003 + A1:2009 | EN 388:2016 2111X | EN 511:2006 111

EN ISO 11640:2012
Dry 150 cycles 4/5 Wet 50 cycles 3/4

www.ejendals.com

TEGERA® 7798

Leather glove, winter-lined, full grain goatskin of top quality, spandex, fleece, Thinsulate™ 40g, Cat. II, black, yellow, reinforced index finger, high visibility colour, for touchscreen, waterproof, reflector, for allround work

PROPERTIES Flexible, durable, excellent grip, perfect fit, extra comfortable

CE Cat. II EN 420:2003 + A1:2009 | EN 388:2016 2111X | EN 511:2006 111

EN ISO 11640:2012
Dry 150 cycles 4/5 Wet 50 cycles 3/4

www.ejendals.com

TEGERA® 7798

Leather glove, winter-lined, full grain goatskin of top quality, spandex, fleece, Thinsulate™ 40g, Cat. II, black, yellow, reinforced index finger, high visibility colour, for touchscreen, waterproof, reflector, for allround work

PROPERTIES Flexible, durable, excellent grip, perfect fit, extra comfortable

CE Cat. II EN 420:2003 + A1:2009 | EN 388:2016 2111X | EN 511:2006 111

EN ISO 11640:2012
Dry 150 cycles 4/5 Wet 50 cycles 3/4

www.ejendals.com

TEGERA® 7798

Leather glove, winter-lined, full grain goatskin of top quality, spandex, fleece, Thinsulate™ 40g, Cat. II, black, yellow, reinforced index finger, high visibility colour, for touchscreen, waterproof, reflector, for allround work

PROPERTIES Flexible, durable, excellent grip, perfect fit, extra comfortable

CE Cat. II EN 420:2003 + A1:2009 | EN 388:2016 2111X | EN 511:2006 111

EN ISO 11640:2012
Dry 150 cycles 4/5 Wet 50 cycles 3/4

www.ejendals.com

TEGERA® 7798

Leather glove, winter-lined, full grain goatskin of top quality, spandex, fleece, Thinsulate™ 40g, Cat. II, black, yellow, reinforced index finger, high visibility colour, for touchscreen, waterproof, reflector, for allround work

PROPERTIES Flexible, durable, excellent grip, perfect fit, extra comfortable

CE Cat. II EN 420:2003 + A1:2009 | EN 388:2016 2111X | EN 511:2006 111

EN ISO 11640:2012
Dry 150 cycles 4/5 Wet 50 cycles 3/4

www.ejendals.com