

## TEGERA® 7798

Leather glove, winter-lined, full grain goatskin of top quality, spandex, fleece, Thinsulate™ 40g, Cat. II, black, yellow, reinforced index finger, high visibility colour, for touchscreen, waterproof, reflector, elasticated 180°, for allround work

### PROPERTIES

Flexible, durable, excellent grip, perfect fit, extra comfortable

### SPECIFICATION

TYPE OF GLOVE Cold insulation gloves, Heavy duty gloves

CATEGORY Cat. II

SIZE RANGE (EU) 7, 8, 9, 10, 11, 12

COLLECTION Dynamic Strength

PALM MATERIAL Full grain goatskin of top quality

BACK MATERIAL Spandex

LINING Winter-lined

LINING MATERIAL Fleece, Thinsulate™ 40g

CLO 0,7 m<sup>2</sup>·K/W

DEXTERITY 5

FASTENING Elasticated 180°

LENGTH RANGE 240-275 mm

COLOUR Black, Yellow

PAIRS PER PACKAGE/CARTON 6/36

DISPLAY Hangtag with euro slot

OUTER MATERIAL SPECIFICATION Polyurethane, polyester, polyester

MIDDLE MATERIAL SPECIFICATION Polyethylene

INNER MATERIAL SPECIFICATION Polyester



AQUATHAN®



**Thinsulate™**  
INSULATION

SIZE	ART. NO.	EAN NO.
7	7798-7	7340118347004
8	7798-8	7340118347097
9	7798-9	7340118347189
10	7798-10	7340118347271
11	7798-11	7340118347363
12	7798-12	7340118347455

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## TEGERA® 7798

### FEATURES

For touchscreen, high visibility colour, reinforced index finger, reinforced fingertips, reinforced thumb, specially designed thumb, waterproof, reflector, specially designed details, elastic

### PREVENTS RISK OF

Blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping, contact with moisture, contact with damp, contact with cold

### PRIMARY ENVIRONMENTS OF USE

Dark environments, windy environments, slippery environments, dry environments, cold environments, wet environments, moist environments, oily and greasy environments, dirty environments, harsh environments

### PRIMARY AREAS OF USE

Agricultural work, airport work, building and construction, carpentry, concrete work, construction, engineering, forest work, gardening, HVAC installation, installation work, machine driving, machine operating, paper industry work, repair work, soil preparation, transport work, warehouse work, wood industry work



### PRIMARY INDUSTRIES OF USE

Agriculture, mining, pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, MRO, automotive, transportation, utilities, building and construction, logistics, HoReCa, facilities, service, retail

### TYPE OF WORK

Medium weight

 Cat. II

EN 420:2003 + A1:2009  EN 388:2016 2111X  EN 511:2006 111

EN ISO 11640:2012 Dry 150 cycles 4/5 Wet 50 cycles 3/4  

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-09-28

2(3)

 **ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

[info@ejendals.com](mailto:info@ejendals.com)

[order@ejendals.com](mailto:order@ejendals.com)

[www.ejendals.com](http://www.ejendals.com)

## TEGERA® 7798

### EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

### COMPLIANCE DESCRIPTION

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	2	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	1	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

### EN 388 - Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 511:2006 Protective gloves against cold

EU 2016/425



CE Cat. II

EN 420:2003  
+ A1:2009



EN 388:2016  
2111X



EN 511:2006  
111

EN ISO 11640:2012

Dry 150 cycles 4/5 Wet 50 cycles 3/4



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-09-28

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com