



SIZE	ART. NO.	EAN NO.
7	874-7	7392626054912
8	874-8	7392626054929
9	874-9	7392626054936
10	874-10	7392626054943
11	874-11	7392626054950

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 874

Synthetic glove, nitrile foam, nitrile-dots, 3/4 dipped, dots, 15 gg, Lycra®, nylon, Cat. II, black, grey, oil and grease resistant palm, for fine assembly work

PROPERTIES

Good fingertip sensitivity, durable, good fit, comfortable, light

SPECIFICATION

TYPE OF GLOVE Assembly gloves

CATEGORY Cat. II

SIZE RANGE (EU) 7, 8, 9, 10, 11

DIPPING 3/4 dipped

DIPPING MATERIAL Nitrile foam, nitrile-dots

LINING MATERIAL 15 gg, Lycra®, Nylon

DEXTERITY 5

GRIP PATTERN Dots

CUFF STYLE Knitwrist cuff

LENGTH RANGE 220 -260 mm

COLOUR Black, Grey

PAIRS PER PACKAGE/CARTON 12/120

PIECES PER BOX 0

DISPLAY Bulk pack

OUTER MATERIAL SPECIFICATION Nitrile

INNER MATERIAL SPECIFICATION Nylon, elastane

TEGERA® 874

FEATURES

Water and oil repellent palm and knuckle

PREVENTS RISK OF

Abrasion injuries, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Oily and greasy environments, dirty environments

PRIMARY AREAS OF USE

Assembly, building and construction, construction, electrical installation, installation work, machine operating, painting, soil preparation

PRIMARY INDUSTRIES OF USE

Machinery and equipment, MRO, automotive

TYPE OF WORK

Light weight

CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
4132X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-06-18

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 874

EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07
France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	4	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	3	(4)
d) Puncturing resistance (N)	2	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
4132X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-06-18

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com