





TEGERA® INFINITY 8803R



Learn more

KNUCKLE DIPPED, DOUBLE COATED PALM

Precision work glove with a unique feeling and ultimate dexterity for jobs in greasy and oily environments. Ultra-light thanks to 18 gg knitting. Knuckle dipped with microfoam coated palm for better grip performance. Withstands contact heat up to 100°C/212°F. Anatomically designed, passes Derma-tests and has Oeko-Tex certificate. Retail packed with descriptive hangtag to help customers with their in-store choice.

CHARACTERISTICS

- Durable
- · Extremely good fingertip sensitivity
- Extra flexible
- Extra comfortable
- Good grip

FUNCTIONS

- Withstands contact heat up to 100°C
- Approved for handling foodstuffs
- Oil and grease resistant
- Thin

PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping, contact with moisture, contact with oil and

PRIMARY ENVIRONMENTS OF USE

Moist environments, oily and greasy environments, dirty environments

PRIMARY AREAS OF USE

Fine assembly, assembly, machine operating, building and construction, carpentry, installation work, hvac installation, engineering, transport work, machine driving, warehouse work, airport work, repair work, service work, shop work

PRIMARY INDUSTRIES OF USE

Machinery and equipment, mro, automotive, transportation, utilities, building and construction, logistics, facilities, service, retail

TYPE OF WORK

Light weight

SPECIFICATION

TYPE Heat protection gloves, Precision work gloves

CATEGORY Cat. II

COLLECTION Infinity

LINING MATERIAL 18 gg, Nylon

LENGTH 235-275 mm

DEXTERITY 5

GRIP DESIGN Foam grip pattern

COLOUR Black, Yellow

PAIRS PER: BUNDLE/CARTON 6/72

DISPLAY TYPE Hangtag with euro slot

DIPPING 3/4 dipped, Double-dipped

DIPPING MATERIAL Nitrile, Nitrile foam, Waterbased PU

CUFF STYLE Knitwrist cuff

CUFF MATERIAL Textile

INNER MATERIAL SPECIFICATION Nylon, Natural latex

OUTER MATERIAL SPECIFICATION Nitrile

COMPLIANCE





TP TC 019:2011

EN 407:2020 (No flame protection)

X1XXXX

information/UIS



388:2016+A1:2018

EN ISO 21420:2020







Contact heat rating valid for palm area only

SIZE		ARTICLE NUMBER	EAN
7	S	8803R-7	7340118368153
8	М	8803R-8	7340118368245
9	L	8803R-9	7340118368337
10	XL	8803R-10	7340118368429
11	XXL	8803R-11	7340118368511



Limavägen 28, SE-793 32 Leksand, Sweden Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com