



Flexible, soft and skin friendly synthetic glove, palm-dipped with nitrile foam.

**TEGERA® 884A**



[Learn more](#)

**TOUCH SCREEN FUNCTION AND GREAT GRIP**

Flexible and soft knitted 15 gg synthetic glove, palm-dipped with nitrile foam and nitrile dots for great grip. Touch screen function. Perfect for precision work, fine assembly work, inspection work, and other kinds of light weight work in dry and moist environments. Withstands contact heat up to 100°C/212°F. Skin friendly with Derma-test and Oeko-Tex certificate.

CHARACTERISTICS	FUNCTIONS
<ul style="list-style-type: none"><li>• Very durable</li><li>• Good fingertip sensitivity</li><li>• Flexible</li><li>• Good grip</li><li>• Comfortable</li></ul>	<ul style="list-style-type: none"><li>• Withstands contact heat up to 100°C</li><li>• For touchscreen</li></ul>

**PREVENTS RISK OF**

Abrasion injuries, grazes, scratches, lacerations, contact with dirt

**PRIMARY ENVIRONMENTS OF USE**

Dry environments, moist environments, dirty environments

**PRIMARY AREAS OF USE**

Fine assembly, assembly, inspection work, machine operating, building and construction, carpentry, painting, installation work, electrical installation, hvac installation, sheet-metal work, tiling, construction, soil preparation, concrete work, engineering, transport work, machine driving, warehouse work, airport work, mining, wood industry work, forest work, agricultural work, gardening, repair work

**PRIMARY INDUSTRIES OF USE**

Agriculture, mining, rubber and plastic, automotive, transportation, utilities, building and construction

**TYPE OF WORK**

Light weight

**SPECIFICATION**

**TYPE** Heat protection gloves, Precision work gloves

**CATEGORY** Cat. II

**LINING MATERIAL** 15 gg, Nylon, Spandex

**LENGTH** 220-260 mm

**DEXTERITY** 5

**GRIP DESIGN** Dots

**COLOUR** Black, Grey

**PAIRS PER: BUNDLE/CARTON** 12/120

**DISPLAY TYPE** Hook with hangtag

**DIPPING** Palm-dipped

**DIPPING MATERIAL** Nitrile foam, Nitrile-dots

**CUFF STYLE** Knitwrist cuff

**CUFF MATERIAL** Textile

**CUT RESISTANCE (EN ISO 13997)** Cut resistance level A



**INNER MATERIAL SPECIFICATION** Nylon, Natural latex, Elastane

**OUTER MATERIAL SPECIFICATION** Nitrile

**COMPLIANCE**



TP TC 019:2011



EN ISO 21420:2020



Contact heat rating valid for palm area only

**FEATURES**



SIZE		ARTICLE NUMBER	EAN
5	XXS	884A-5	7340118381282
6	XS	884A-6	7340118381435
7	S	884A-7	7340118322254
8	M	884A-8	7340118322261
9	L	884A-9	7340118322278
10	XL	884A-10	7340118322233
11	XXL	884A-11	7340118322230
12	3XL	884A-12	7340118322247

**ejendals**

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com