



## TEGERA® 909

Cut resistant glove, PU, palm-dipped, smooth finish, cut resistance level B, 18 gg, Dyneema® Diamond Technology, Lycra®, nylon, Cat. II, grey, water and oil repellent palm, for precision work

### PROPERTIES

Extremely good fingertip sensitivity, extra flexible, breathable

### SPECIFICATION

TYPE OF GLOVE Cut resistant gloves

CATEGORY Cat. II

CUT RESISTANCE (EN ISO 13997) Cut resistance level B

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 5.9

SIZE RANGE (EU) 5, 6, 7, 8, 9, 10, 11

DIPPING Palm-dipped

DIPPING MATERIAL PU

LINING MATERIAL 18 gg, Dyneema® Diamond Technology, Lycra®, Nylon

DEXTERITY 5

GRIP PATTERN Smooth finish

CUFF STYLE Knitwrist cuff

LENGTH RANGE 210-250 mm

COLOUR Grey

PAIRS PER PACKAGE/CARTON 12/120

PIECES PER BOX 0

DISPLAY Bag with euro slot

OUTER MATERIAL SPECIFICATION Polyurethane

INNER MATERIAL SPECIFICATION UHMWPE, nylon, elastane

1(3)



SIZE	ART. NO.	EAN NO.
5	909-5	7340118329406
6	909-6	7340118300320
7	909-7	7340118300344
8	909-8	7340118300368
9	909-9	7340118300382
10	909-10	7340118300283
11	909-11	7340118300306

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## TEGERA® 909

### FEATURES

Water and oil repellent palm, steel-fibre free, fibreglass-free

### PREVENTS RISK OF

Cut injuries, scratches, lacerations, contact with dirt

### PRIMARY ENVIRONMENTS OF USE

Cut risk environments, dry environments, dirty environments

### PRIMARY AREAS OF USE

Building and construction, construction, fine assembly, inspection work, installation work, metalwork


### PRIMARY INDUSTRIES OF USE


Pulp and paper, rubber and plastic, metal fabrication, automotive, logistics

### TYPE OF WORK

Light weight

**CE** Cat. II

 EN 420:2003  
+ A1:2009

 EN 388:2016  
3X42B



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-09-07

**ejendals**  
PROTECTING HANDS AND FEET

### EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

# TEGERA® 909

## EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07  
France

## COMPLIANCE DESCRIPTION

ANSI/ISEA 105-2016 Cut resistance according to the American National Standard Institute 105-2016. Levels A1-A9

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	3	(4)
b) Cut resistance (Index)	X	(5)
c) Tear resistance (N)	4	(4)
d) Puncturing resistance (N)	2	(4)
e) Cut resistance, EN ISO 13997 (N)	B	(F)
f) Impact protection, EN 13594:2015		(P)

## EN 388 - Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425



CE Cat. II

ANSI A2 CUT EN 420:2003 + A1:2009

EN 388:2016 3X42B



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-09-07

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com